

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number  
**WO 2004/044315 A1**

(51) International Patent Classification<sup>7</sup>: D21G 7/00 // 1/00

(21) International Application Number:  
PCT/FI2003/000852

(22) International Filing Date:  
11 November 2003 (11.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
20022017 12 November 2002 (12.11.2002) FI

(71) Applicant (for all designated States except US): METSO  
PAPER, INC. [FI/FI]; Fabianinkatu 9 A, FIN-00130  
HELSINKI (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): PULLINEN,

Hannu [FI/FI]; Kuuselanatie 27, FIN-11130 RIIHIMÄKI  
(FI). HAAG, Jorma [FI/FI]; Pikitie 12, FIN-03620  
KARKKILA (FI).


(74) Agent: BERGGREN OY AB; P.O. BOX 16, FIN-00101  
HELSINKI (FI).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,  
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,  
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,  
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,  
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,  
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

[Continued on next page]

(54) Title: MOISTENING ARRANGEMENT OF MULTIPLE-NIP CALENDER



(57) Abstract: The invention relates to a moistening arrangement of a multiple-nip calender (1), by means of which a fibre web (W) to be calendered in a multiple-nip calender is moistened, the multiple-nip calender comprising a set of rolls (2) with roll nips (N) between the rolls, at least one of the rolls being a reversing nip and the moistening arrangement including a roll means (3) for moistening the fibre web. The roll means is located in a pocket (7) adjacent to the line (L) of the aligned set of rolls, the pocket being formed by a space defined by the fibre web (W), one idle roll (5) in the set of rolls and said roll means (3), the fibre web contacting said roll in the set of rolls at two locations, in roll nips located on opposite sides of the roll mantle when viewed from the longitudinal axis of the roll, and circulating around the roll means (3). The fibre web (W) contacts said roll in the set of rolls preferably in the roll nip immediately preceding the reversing nip (N;N3). The roll means (3) comprises a damping unit (33) and rolls (32) guiding the fibre web (W) relative to the damping unit.

● O 2004/044315 A1



SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*

## Moistening arrangement of multiple-nip calender

5 The invention relates to a moistening arrangement of a multiple-nip calender as defined in the preamble of claim 1.

10 Multiple-nip calenders comprise a plurality of nips formed between the polymer roll and the heated steel roll. While passing between the roll nips, the fibre web is calendered at its surface. Should it be desirable to calender both sides of the fibre web with a multiple-nip calender disposed in one frame, a "reversing nip" comprising two successive polymer rolls must be provided in the multiple-nip calender. The calendered fibre web should have as equal quality as possible both in the lateral and the longitudinal direction of the fibre web, and the fibre web consequently requires moistening both before entering the multiple-nip calender and 15 while proceeding in the multiple-nip calender. Usually 1 to 4 fibre web damping units are disposed in a multiple-nip calender, the number of damping units depending principally on the number of nips in the calender and on the fact whether the calender has been disposed in one or two frames. With an increase of the number of roll nips in multiple-nip calenders, the fibre web will require increased 20 damping. A reversing nip also requires increased damping of the fibre web, because both sides of the fibre web will require damping: usually damping is carried out in multiple-nip calenders equipped with a reversing nip just before the fibre web enters the multiple-nip calender, before the reversing nip. Damping that takes place before the reversing nip is usually performed by means of a damping unit disposed in "a pocket" between the output roll and the set of rolls. In multiple-nip calenders, the set of rolls is usually placed within a very narrow area, and for the fibre web to be efficiently moistened in the pocket, the number of damping units must be increased. The narrow pocket cannot accommodate very large and efficient damping units, because it already accommodates the crown variation means of the idle roll, and 25 also auxiliary means such as steam boxes, in addition to the piping of the fibre web damping unit. Any attempts to solve the problem by enlarging the pocket with the output roll transferred further away from the line of the aligned set of rolls would risk generating vibrations caused by the increased torque of the output roll.

35 The purpose of the invention is to eliminate the prior art shortcomings described above. Consequently, the chief purpose of the invention is to provide a fibre web moistening arrangement in a multiple-nip calender equipped with a reversing nip,

the moistening arrangement allowing for efficient location of the damping unit in the pocket of the multiple-nip calender.

5 The invention has the additional purpose of decreasing the number of fibre web damping units in multiple-nip calenders.

The moistening arrangement defined in claim 1 achieves the purposes mentioned above.

10 The damping arrangement of a multiple-nip calender of the invention, by means of which a fibre web to be calendered in a multiple-nip calender is moistened, comprises a set of rolls with roll nips between the rolls. The damping arrangement includes a roll means for damping the fibre web, which is located in a pocket adjacent to the line of the aligned set of rolls, the pocket consisting of a space  
15 defined by the fibre web, one of the idle rolls in the set of rolls and said roll means. The fibre web contacts this roll in the set of rolls at two locations, approximately at roll nips located on opposite sides of the roll mantle, viewed from the longitudinal axis of the roll, and the fibre web also circulates around the roll means. The roll means comprises a damping unit and also rolls guiding the fibre web relative to the  
20 damping unit. In a preferred embodiment, the fibre web touches this roll in the set of rolls in the roll nip located immediately before the reversing nip.

In this application, a reversing nip implies the roll nip formed between two  
25 polymer-coated rolls.

The invention is based on the fundamental idea of the output roll in a multiple-nip calender being replaced with a roll means, which comprises two guide rolls with relatively small diameter on each side of the frontal face of the damping unit (the surface through which water is sprayed). In this manner, an efficient and relatively  
30 large-sized damping unit can be accommodated in the otherwise narrow pocket of a multiple-nip calender. In a preferred embodiment of the invention, the guide rolls consist of a plurality of successive roll sections.

35 The moistening arrangement of the invention achieves several advantages over corresponding prior art arrangements for fibre web damping. Thus the nip vibrations of the set of rolls are reduced when an output roll with relatively large diameter is replaced with guide rolls having significantly smaller diameter and bulk,

which are located in the damping roll means. There is no need to enlarge the pocket by transferring the output roll further out from the nip rolls, and thus increased nip vibrations are further avoided. A large-sized and efficient damping unit receivable in the pocket allows for a reduced number of damping units, resulting in a smaller number of piping and device units within the narrow roll area. The service distances to the set of rolls can also be maintained.

The invention is described below with reference to the accompanying figure 1.

Figure 1 shows schematically a set of rolls 2 in a multiple-nip calender 1, viewed directly from the end of the set of rolls. For the sake of clarity of the figure, the multiple-nip calender is shown in the figure devoid of the calender frame, the fibre web guide rolls, the load compensating means of the idle rolls, the upper and lower roll loading means and auxiliary means such as steam boxes. The multiple-nip calender illustrated in the figure is conventional with respect to these structures.

The set of rolls 2 of the multiple-nip calender 1 of figure 1 comprises six rolls. The outside of the set of rolls is located on the left of the central line L of the set of rolls, whereas the inside of the set of rolls is located on the right side. Consequently, the fibre web enters the set of rolls from the inside of the set of rolls and leaves the set of rolls to the outside. Both the uppermost and the lowermost roll 4;4' and 4;4'' are equipped with hydraulic loading means within the roll for control of the nip pressure in the set of rolls and also for control of the nip pressure profile. Idle rolls 5, i.e. rolls 5'..5''' are alternately water-heated steel rolls with a hard surface and polymer-coated rolls. Polymer-coated rolls are thus rolls 4', 5'', 5''', 4'', and steel rolls are rolls 5' and 5'''. The ends of the idle rolls 5 comprise hydraulic roll crown variation means, which serve for complete or partly compensating roll crowning caused by the inherent roll mass and by the auxiliary means at the roll ends, in order to maintain the desired nip pressure profile of the multiple-nip calender. The crown variation means have a design that is conventional *per se*, such means being described e.g. in "*Wochenblatt für Papierfabrikation, Heft 23/24 1997*" and in other literature in the field. The set of rolls 2 exemplified in the figure comprises five roll nips N, of which the central nip N;N3 is a "reversing nip" for control of a single-sided fibre web. The idle rolls 5'' and 5''' on different sides of the reversing nip are both polymer rolls. The line L of the set of rolls, i.e. the line L passing through the central point of the rolls in the set of rolls, is in a substantially vertical position. The roll nips N:N2, N;N4 and N;N5 are preceded by output/spreading rolls 6 in the

calender, these rolls serving to spread the fibre web and to act on the period over which the heat of the thermo-roll acts on the fibre web before the fibre web reaches the following roll nip. In addition, these output/spreading rolls are used for removing folds on the fibre web. The spreading/output rolls 6 also equalise the distance between two successive roll nips over which the fibre web W travels in the machine cross- direction. The output roll located before the reversing nip N<sub>2</sub>;N<sub>3</sub> has been replaced with a roll means 3. In this roll means 3, the same frame 31 comprises attached fibre web damping unit 33 and guide rolls 32 steering the fibre web relative to the damping unit. The guide rolls 32 have a diameter notably smaller than that of the spreader rolls 6. Each guide roll 32 consists of "sectional rolls", which are formed by short successive guide rolls mounted in the same frame and having identical diameters. The guide rolls 32 are disposed relative to the damping unit 33 so that the surface of the fibre web W passes in the vicinity of the frontal face 33a of the damping unit, the water jets being fed through this frontal face. The damping unit 33 may have a design that is conventional *per se*, such as a design with two nozzle rows on the frontal face of the damping unit, each nozzle row comprising a plurality of small nozzles. Small water droplets are conducted through the nozzles so as to moisten the fibre web surface passing in the vicinity of the frontal face. For a more detailed description of the design of the damping units, we refer to prior art and to the applicant's damping unit of the range VIBAir Tech™, for instance.

A roll means 3 of the kind described above is located in the pocket 7 adjacent to the set of rolls 2. The pocket is formed in a space where the fibre web contacts the idle roll 5" (the mantle of the idle roll) in roll nips N<sub>2</sub>;N<sub>2</sub>' and N<sub>2</sub>;N<sub>3</sub>' and circulates around the roll means 3 via the guide rolls 32; 32' and 32;32". The roll means 3 is at a suitable distance from the line L of the aligned set of rolls. The roll nips N<sub>2</sub>;N<sub>2</sub>' and N<sub>2</sub>;N<sub>3</sub>', in which the idle roll 5" is closest to the adjacent idle rolls 5' and 5"', are located roughly on opposite sides of the mantle of the idle roll 5", viewed from the longitudinal axis of the idle roll. The roll nip N<sub>2</sub>; N<sub>3</sub>' is a "reversing nip", which is located between two polymer-coated idle rolls 5" and 5'''. The roll nip N<sub>2</sub>, in turn, is located between the heated thermo-roll 5' (steel-coated idle roll) and the polymer-coated idle roll 5".

Placing a roll means 3 comprising a damping unit 31 of the kind described above in the pocket 7 to replace the spreader roll, which is usually located in this pocket,

yields the appreciable advantage of allowing the damping unit and also its moistening performance to be adequately dimensioned.

- 5 The performance of the damping unit is usually directly proportional to the area through which water is sprayed (frontal face). Should the same pocket accommodate both an output roll and a damping unit, beside other auxiliary means in the pocket and also load compensating means, the damping unit would have to be dimensioned with smaller size and lower output, which would require an increased number of damping units. Optionally, the pocket 7 could be given a larger size by
- 10 transferring the output roll 6 outwardly from the line L of the set of rolls, however, this would risk causing problems due to vibrations, which are generated by the increased torque of the guide roll and exerted on the frame of the multiple-nip calender.
- 15 One single moistening arrangement of the invention has been described above, yet it is obvious to those skilled in the art that the invention can be implemented in many other ways as well, without departing from the scope of the inventive idea defined in the claims. The arrangement of the invention can thus be used also in multiple-nip calendars with a divided frame. In such multiple-nip calendars, the fibre web
- 20 requires damping, because the fibre web tends to dry over the web feeding from the first part to the second part of the set of rolls.

## Claims

1. Moistening arrangement in a multiple-nip calender (1) for moistening a fibre web (W) to be calendered in a multiple-nip calender, the multiple-nip calender comprising a set of rolls (2) with roll nips (N) between the rolls, the moistening arrangement including a roll means (3) that moistens the fibre web and is located in a pocket (7) adjacent to the line (L) of the set of rolls, the pocket being formed by a space defined by the fibre web (W), one of the idle rolls (5) in the set of rolls and said roll means (3), the fibre web contacting said roll in the set of rolls at two locations, approximately in roll nips on opposite sides of the roll mantle, when viewed from the longitudinal axis of the roll, and circulating around the roll means (3), **characterised** in that the roll means (3) comprises a damping unit (33) and rolls (32) guiding the fibre web (W) relative to the damping unit.
2. Moistening arrangement as defined in claim 1, **characterised** in that the fibre web (W) contacts said roll in the set of rolls in the roll nip located immediately before the reversing nip (N; N3).
3. Moistening arrangement as defined in any of the preceding claims, **characterised** in that the line (L) of the set of rollers is advantageously vertical or at an angle to the horizontal plane.
4. Moistening arrangement as defined in any of the preceding claims, **characterised** in that the roll means (3) comprises a frame, to which a damping unit (31) and rolls (32) guiding the fibre web relative to the damping unit are attached.
5. Moistening arrangement as defined in any of the preceding claims, **characterised** in that the roll means comprises two guide rolls (32), which are located on each side of the frontal face (33a) of the damping unit, in parallel with the longitudinal axis of the damping unit.
6. Moistening arrangement as defined in any of the preceding claims, **characterised** in that the guide rolls (32) consist of a plurality of successive roll sections.






Fig. 1

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/FI 03/00852

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 D21G7/00 //D21G1/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 D21G D21F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 642 164 A (KALLIOLA LAURI ET AL) 10 February 1987 (1987-02-10) column 3, line 11 - line 22; figure 1	1-6
A	US 3 782 330 A (KANDA M) 1 January 1974 (1974-01-01) column 2, line 4 - line 8 column 2, line 57 - line 60 column 3, line 53 - column 4, line 9	1-6

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

24 February 2004

Date of mailing of the international search report

11 03. 2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

ERIKA WESTBERG / ELY

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/FI 03/00852

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4642164	A	10-02-1987	FI 840515 A	09-08-1985
			AT 388197 B	10-05-1989
			AT 31585 A	15-10-1988
			CA 1243871 A1	01-11-1988
			DE 3503448 A1	08-08-1985
			IT 1183223 B	15-10-1987
			SE 462922 B	17-09-1990
			SE 8500468 A	09-08-1985
-----				
US 3782330	A	01-01-1974	NONE	
-----				